la marzocco

leva



LEVA reimagining what a lever-actuated espresso machine can be

AVAILABLE CONFIGURATIONS

no. groups:

configurations: LEVER (leva s, leva x)

Featuring eye-catching design and a lower profile to invite customer interaction, Leva re-invents the iconic lever machine design with more ergonomic elements. Leva is a cuttingedge café centerpiece that encourages engagement, barista experimentation, and coffee conversations, while delivering a delicious coffee extraction.

Leva brings with it design, focusing not just on physical beauty, but also on the satisfaction found in a truly mechanical system.

LEVA HIGHLIGHT

live pressure visualization (leva x only)

The Leva is equipped with dedicated graphical displays for each group. The displays provide live visualization of pre-infusion pressure, extraction pressure, and time throughout the course of the shot. After the coffee has been delivered, the extraction curve and parameters are visualized on the displays as a graph. The barista has the ability to overlay past visualizations, saving up to four graphs for each group, as guides for future extractions

FEATURES

independent brew boilers (leva x)

Separate boilers for each group head allow baristas to optimize temperature for individual coffees

smart PID (leva x)

An advanced PID controller greatly improves the machine's temperature stability

pro touch steam wands

Vacuum-insulated double-walled steam wands remain cool while delivering high-volume dry steam

ECO mode

Boiler temperatures reduce to lower set-points after extended idle periods, improving energy efficiency

military-grade steam potentiometer (leva x)

Proportional steam valves facilitate machine usability and maintenance while improving its durability

SPECIFICATIONS	2 group	3 group
dimensions (W x D x H)	31.5" x 25.5" x 30.5"	40" x 25.5" x 30.5"
weight (lbs)	218	284
voltage (VAC, phase, Hz)	208-240, 1, 60	208-240, 1, 60
element wattage	5400 (Leva S), 5700 (Leva X)	6800 (Leva S), 7800 (Leva X)
steam boiler capacity (liters)	8.2	11.8
brew boiler capacity (liters)	3.4 (Leva S), 1.3 x2 (Leva X)	5 (Leva S), 1.3 x3 (Leva X)
amp service required	30	50
certifications	UL-197, NSF-8, CAN / CSA-C22.2 No. 109	